







Our FLUXX® Caps can be used for a variety of thread sizes. For this purpose, the specified container threads must meet the dimensional requirements of our Caps. The dimensional accuracy of the individual product solution must be observed and can be found in the tables below.

	DIN 38	DIN 40	DIN 45	DIN 50	DIN 51	DIN 61	DIN 63	DIN 71
Ø A *1	1.406 in.	1.496 in.	1.598 in.	1.811 in.	1.921 in.	2.138 in.	2.339 in.	2.559 in.
Ø B *2	1.480 in.	1.646 in.	1.740 in.	1.949 in.	2.106 in.	2.343 in.	2.500 in.	2.795 in.
Ø C ∗3	1.142 in.	1.299 in.	1.378 in.	1.555 in.	1.717 in.	1.909 in.	2.165 in.	2.260 in.
‡ P*4	0.118 in.	0.157 in.	0.157 in.	0.157 in.	0.197 in.	0.236 in.	0.167 in.	0.276 in.


## Outer dimensions





	R ¾" BSP thread	BCS 70x6 rough thread	BCS 56x4 rough thread	PPS 2" fine thread
Ø A *5	0.976 in.	2.520 in.	2.043 in.	2.228 in.
Ø B *6	1.138 in.	2.756 in.	2.244 in.	2.331 in.
‡ P *7	0.071 in.	0.236 in.	0.157 in.	0.091 in.

## Inner dimensions



## **Application examples**

- Liquid food
- Chemicals
- Agrochemicals
- Cleaners
- Hygiene and care products



**Tolerances:**  $^{11} \pm 0.012$  in.;  $^{12} \pm 0.012$  in.;  $^{13} \pm 0.028$  in.;  $^{14} \pm 0.004$  in.;  $^{15} \pm 0.012$  in.;  $^{16} \pm 0.012$  in.;  $^{17} \pm 0.004$  in.

The information regarding dimensional accuracy is intended to support measurement procedures for identifying suitable product solutions. When adapting or building new tools, the dimensional accuracy has to be aligned with the market-specific standardization. The dimensional accuracy must always be checked on a case-by-case basis. Our experts will be pleased to advise you.



## Notice

Please visit our website www.fluxx-sabeu.com for the latest and most up-to-date information. The information provided in this document herein is subject to change at any time without notification. This document does not commit SABEU in any way. SABEU is not responsible for any errors that may appear in this document.